

产品特性/Product Features

- IP6K9K
- 400A 85°C长时间载流能力
- 12-750VDC
- 1000MΩ (1000VDC) , IEC 60664-1
- PCB

触点参数 / Contact parameters

		1a	
		≤0.5mΩ (at 400A)	
		400A	
		2×10 ⁵	
		450V型	750V型
		1000VDC	1000VDC
		2500A(320VDC)1	2500A(320VDC)1
		180kW	300kW
1)		2×10 ⁴ 22.5VDC, =1ms 500A, 400A	1×10 ⁵ 37.5VDC, =1ms 500A, 400A
		1 360VDC, =1ms 1350A, 400A	
		1×10 ⁵ 450VDC,80A	1×10 ⁵ 750VDC,80A
		: 2×10 ⁵ 450VDC,400A	: 1×10 ⁵ 750VDC,400A
2)		400A:	
		600A:20min	
		1200A:30s	
		3000A:0.6s	


1) 23°C, 0.6s:5.4s,

2) 85°C, 120 mm², - - - - -

		1000MΩ(1000VDC)
		3000VAC 1min
		3000VAC 1min
	()	≤30ms
	()	≤10ms
		196m/s ²
		490m/s ²
		10Hz ~ 500Hz 49m/s ²
		5% ~ 85%RH
		-40°C ~ 85°C
		M6
		700g
		93.0mm×65.1mm×74.9mm

VDC	VDC	VDC	W
12	9	3.6	45(0.2s) 3.8
24	≤18	≥7.2	45(0.2s) 3.8

-40°C ~ 85°C)




安装孔尺寸 / 接线图 Mounting hole size/Wiring diagram

Mounting hole size


Wiring diagram

线圈引出形式 Coil take-up form




性能曲线图 Performance graph

Electrical life curve



Tolerance curve



使用注意事项 Precautions for use

- 1 9N·m~11N·m M5 3N·m~4N·m

M6螺钉	9N·m~11N·m	Ø6.0~Ø6.5mm	6mm	M5螺钉	3N·m~4N·m

- 2 120mm²
3 0.2s 0.2s
4
5 3mm



声明/Statement:

- 1.
- 2.